

Annex-B						
REHABILITATION AND EXTENSION OF DWSS AT KILLI SAKHI SULTAN UC JANGIYAN WASHUK						
CIRCULOR TANK 10 FT INTERNAL DIA AND STOARGE CAPACITY OF 3500 US GALLON						
S.N	Description of Work	Quantity	Unit	Brand Offered	Unit Price	Total Price
1	<b>Excavation</b>					
	Excavation in foundation of bridges and other structures, dug belling, dressing, refilling dug belling, dressing, refilling around the structure with excavated earth. Watering ramming lead upto 30m lift upto 1.5m.	488.63	Cft			
2	<b>Lean Concrete 1:4:8</b>					
	Providing and laying plain machine mixed cement concrete using coarse sand and crushed aggregate having maximum size upto 1-1/2" (38mm) & down gauge in foundation including levelling, compacting and curing. 1:4:8	113.81	Cft			
3	<b>Concrete 1:2:4</b>					
	Providing and laying plain machine mixed cement concrete using coarse sand and crushed aggregate having maximum size upto 1-1/2" (38mm) & down gauge in foundation including levelling, compacting and curing. 1:2:4	220.13	Cft			
4	<b>Brick Work</b>					
	Providing and laying first class solid burnt brick masonry (Brick Strength:1800psi-2000psi) including scaffolding, raking out joints and curing in ground floor superstructure and i/c cost of testing Upto 4.5" (115 mm) nominal thick brick work Cement sand 1 : 3	396.23	Cft			
5	<b>Plaster</b>					
	Cement plaster using coarse sand on soffit of ceiling , cantilever slabs, sides and soffits or beams in basement and ground floor including making edges , comers and curing.	575.22	Sft			
6	<b>Steel</b>					
	Providing, fabricating and laying deformed Grade 40 steel reinforcement (deformed bar) for all kinds of R.C.C work in foundation, plinth and ground floor including the cost of straightening, removal of rust, cutting, bending, binding, wastage and providing such over-laps as are not shown on the drawings. The cost of binding wire and cement concrete spacer blocks or chairs for binding and holding the reinforcement in position is inclusive upto 15 ft. (5m)height	0.35	Tonne			
7	<b>Tank Cover</b>					
	Supply & fitting CI main hole cover with frame weight not less than 50Kg per Sqm I/c locking arrangement.24" Square	1.00	No			
8	<b>Air Vent Pipes</b>					
	Providing and fixing air vent pipes 4" dia. With wire mesh.	2.00	No			
9	<b>Weather Resistant Paint</b>					
	Applying weather resistant paint coating such as ICI/ Berger or equivalent paint of approved shade on old surface of walls and ceiling including dusting, sand papering and cleaning, scaffolding and removal of debris.	285.92	Sft			
10	<b>G I Pipe 100 mm</b>					
	Supplying G.I. pipe IIL or equivalent make registered with PSQCA including the cost of specials and cost of bitumen for 2 coats and specials.	25.00	Rft			
11	<b>HDPE Pipe 50 mm</b>					
	Supplying HDPE pipes density 700-960 kg/cu.m and carbon black contents > 2% with DIN-8074, 8075 or PS-3580:1997(rev.) ISO 9001-2000 pressure classification of PE -100 (black) for water PN-12.5 including specials and valves. 50 mm	150.00	Rft			
12	<b>Bib Cock</b>					
	Providing and fixing of bib cock 3/4" dia on G-I pipe 3" dia feet long i/c band,tee,etc complete in all respect.	7.00	Job			
13	<b>Sign Board</b>					
	Supply and Installation of 01 Sign Board Complete in all Respect and as per IR Design.	1.00	Job			
Total Amount (Inclusive of all Govt applicable Taxes, Deliveries, Transportations and Installation, if any						